

FC

SERIES

10-800 kVA

3:3
PHASE

FREQUENCY CONVERTER



AIRPORT



DATA CENTER



MEDICAL



TRANSPORT



INDUSTRY



EMERGENCY



TOWER



POWER FACTOR



SERVICE



FEATURES

- True Two Level (2L) or True Three Level (3L) IGBT PWM Rectifier & Inverter Technology
- Output Power Factor 0.9 (*Optional 0.7-1.0*)
- DSP Control
- Ultra High Efficiency up to 96%
- Low Input Current THD (<3%)
- High Input Power Factor (>0.99)
- Wide Input Voltage Range (*Optional*)
- Short Circuit and Overload Protection
- Parallellable Modules up to 8 units
- 1500 Real Time Event Log with Detailed Parameters
- Static&Manual Bypass Operation (*Optional*)
- Small Footprint and Easy Maintenance
- Advanced Communication Capabilities
- Perfect Generator Compatibility
- EPO (Emergency Power Off)
- Capacitive Kit Option (*Optional*)
- Auto Restart
- High Efficiency & Low Operating
- CostShort MTTR (Mean Time To Repair)
- Backfeed Protection



The LEVELUPS Series is attested by Bureau Veritas with regard to performance (EN 62040-3)



POWER
FORLIFE

Aytemiz
MAKELSAN
Uninterruptible Power Supplies

MODEL																			
Capacity		10kVA	15kVA	20kVA	30kVA	40kVA	60kVA	80kVA	100kVA	120kVA	160kVA	200kVA	250kVA	300kVA	400kVA	500kVA	600kVA	800kVA	800kVA
Power Watt		9kW	13.5kW	18kW	27kW	36kW	54kW	72kW	90kW	108kW	144kW	180kW	225kW	270kW	360kW	450kW	540kW	720kW	800kW
INPUT																			
Nominal Voltage		400 VAC 3 Phase +N																	
Voltage Tolerance		-20% +15%																	
Frequency Tolerance		50 / 60 Hz ±10% (Selectable)																	
Power Factor		>0.99																	
Total Harmonic Distortion		THDi <%3																	
OUTPUT																			
Power Factor		0.9 (Optional 0.7-1.0)																	
Nominal Voltage		380/400/415 VAC 3 Phase + N																	
Voltage Tolerance		Static ±1, Dynamic ±3																	
Frequency Tolerance		50Hz / 60Hz ±0,01%																	
Output THD		Linear Load <1% / Non-Linear Load <3%																	
Crest Factor		3:1																	
Overload Capacity*		At 125% Load 10min, at 150% Load 1min																	
Efficiency (Online Mode)		Up to 96%																	
Efficiency (Eco Mode)		Up to 99%																	
BYPASS (Opsiyonel)																			
Nominal Voltage		Depends on External Source.																	
Voltage Tolerance		Depends on External Source.																	
Frequency		Depends on External Source.																	
Frequency Tolerance		Depends on External Source.																	
ENVIRONMENTAL																			
Operating Temperature		0°C / +40°C																	
Storage Temperature		-15°C / +45°C																	
Protection Class		IP20 (Other IP Options are Optional)																	
Humidity		0-95% Without Condensation																	
Altitude		<1000m, Correction Factor 1. <2000m, Correction Factor >0.92, <3000m; Correction Factor >0.84																	
Noise Level		<53 dBA	<55 dBA	<60 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA	<65 dBA
COMMUNICATION																			
Communication Port		RS232 (Standart), RS485, MOD-Bus, J-Bus, Web, Tel-Net, GPRS, CAN-Bus, SNMP (Option)																	
STANDARDS																			
Quality		ISO 9001, ISO 14001, ISO 18001, TSE-HYB																	
Performance		EN62040-3 (VFI-SS-111, Bureau Veritas Certified)																	
EMC/LVD		EN62040-2, EN62040-1, EN60950, (TÜV SÜD Certified)																	
DIMENSIONS & WEIGHT																			
Cabinet Dimensions (mm)	Width	490					763		810		830			1250			1999		
	Depth	805					771		820		870			845			867		
	Height	1190					1555		1705		1800			2102			2045		
Net Weight (kg)		100	100	107	118	125	260	270	350	355	450	460	470	850	850	850	1740	1740	1990
Packaging Dimensions (mm)	Width	600					600		900		900			1370			2150		
	Depth	900					900		970		970			870			970		
	Height	1400					1400		2040		2040			2120			2120		
Gross Weight (kg)		140	141	145	164	185	353	361	376	387	398	491	500	890	890	890	1820	1820	2070

* under certain conditions.
3 Phase In / 1 Phase Out Version is Available. (10 to 30kVA)

Aytemiz-Makelsan reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Aytemiz-Makelsan products previously or subsequently sold. Aytemiz-Makelsan does not guarantee the items of the accuracy and completeness.